

# EasyPART<sup>®</sup>

**Expendable Foam Stop Fire EI 120**  
**Sealing 4.5l Useful Volume**

## APPLICATION

EasyPART<sup>®</sup> is the ideal solution for the stop fire sealing of openings of small and average dimensions. (cable ou cable shelf). EasyPART<sup>®</sup> makes it possible to restore the stop fire degree of netting and paving quickly and easily.

## CHARACTERISTIQUES

- Two-component cartridge charged with a useful volume of 4,5l (cartridge of 400ml).
- Two-component foam stop fire expendable under the effect of heat(EI 120).
- Halogen-free product.
- Very strong expansion during the application(6.5 times).

## ADVANTAGES

- Expendable foam taking the place melted under the effect to heat
- No need for specific training for the application.
- Safe environment.
- Aesthetic of the sealing(draught proofing)
- Easy to use.

## BENEFITS

- Economical profits.
- Protects goods and people during 2 hours.
- Takes part in durable development.
- Colour of the sealing in harmony with the environment of the buildings.

## STORAGE

Store in the original container in a dry place between 5°and 30°C. Check the date of use on packing.

## REMARKS

In order to facilitate the implementation,a framework can be made either in cardboard or with cling film. Foam should not be exposed to the weather. The regulations of the test certification must be respected at the time of the setting in conformity with the fitting.

## HYGIENE/SAFETY/ENVIRONMENT

During the application of foam,the wearing of glasses, safety gloves is recommended. Keep the product out of the reach of children. Dispose of the packing in appropriate containers.

## FIRE TESTS

EasyPART<sup>®</sup> benefits from the certificate of CTICM according to the new European regulation.

This certificate mentions a degree of stop fire of 2 hours (EI 120).

Certificate available on Internet setting: [www.compart.fr](http://www.compart.fr)

## OPERATING INSTRUCTIONS

**1. Take the cartridge out of packing,then unscrew the cap of the cartridge.**



**2. Screw on the mixer at the end of the cartridge using the cap of the cartridge unscrewed previously.**



**3. Press on the tongue of the pistol then arm the dispenser at the back.**



**4. Put the cartridge into the pistol and extract foam by pressure of the pliers until a homogeneous grey colour is obtained.**



**5. Fill the opening completely with EasyPART<sup>®</sup>foam (one cartridge=4,5l).**



**6. Then, place the fire stop sealing label.**



COMPART SAS

78, rue André Boulle 30100 Ales

Service client : 08 260 20 960 Fax : 04 66 566 345

E-mail : [contact@compart.fr](mailto:contact@compart.fr) Site web : [www.compart.fr](http://www.compart.fr)